

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 December 2004 (29.12.2004)

PCT

(10) International Publication Number
WO 2004/113787 A1

(51) International Patent Classification⁷: **F17C 13/12**

(21) International Application Number:
PCT/KR2004/001519

(22) International Filing Date: 24 June 2004 (24.06.2004)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:
10-2003-0041132 24 June 2003 (24.06.2003) KR

(71) Applicant (for all designated States except US): DAE
RYUK CAN CO., LTD. [KR/KR]; 733-25, Yeoksam
2-dong, Gangnam-gu, Seoul 135-082 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): YOUM, Don-Woo
[KR/KR]; 723-502, Mokdong Apt. 7-Danji, 926, Mok

1-dong Yangcheon-gu, Seoul 158-757 (KR). KIM,
Byoung-Gu [KR/KR]; 482, Yugu-ri 2-gu, Yugu-eup,
Gongju-si, Chungcheongnam-do 314-895 (KR). GIL,
Do-Young [KR/KR]; C-203, Munhyeon House, Munhyeon
3-dong, Nam-gu, Busan 608-043 (KR).


(74) Agent: NAM, Sang-Sun; 9th Fl., Maekyung Media Cen-
ter, 30, 1-ga, Pil-dong, Jung-ku, Seoul 100-728 (KR).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: A SMALL SIZED AND HIGH-PRESSURIZED CONTAINER FOR PREVENTING EXPLOSION



(57) Abstract: The present invention discloses a small sized and high-pressurized container for preventing explosion. According to the preferred embodiment of the present invention, a can body has a shape of cylinder for containing high-pressurized product therein. An upper body, which has a dome-like shape, is connected to the top of the can body by seaming or welding, and comprises a groove around its lower part. A valve is mounted on the top of upper body, and discharges high-pressurized gases or liquids, which exists in the inside of the container. A plurality of scores is configured at the bottom of the groove of the upper body, in order to discharge an overpressurized product and prevent bursting or explosion of the container. The scores weaken the resistance of the upper body, so in the event of that a certain internal overpressure is applied, the upper body firstly deforms outwardly and then one or more scores are fractured, and lastly the overpressurized product is discharged from the scores.

WO 2004/113787 A1



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

— before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*